Product Datasheet

HDPE CONSTRUCTION NET

CHARACTER	UNIT	SPECIFICATION	TEST METHOD
Material	----	100% Virgin HDPE	-------
Colour	----	WHITE	-------
Shade factor	%	70%	ASTM D 17-46
Yarn type (weft)	---	Tape	----
Yarn type (warp)	----	Tape	----
Yarn thickness	mícron	29	----
Yarn density- Pillar stitch	per cm.	3.27	
Weight	Gr/Sq.m.	70 +/-5%	ASTM D 3776
UV Stabilitv	Years	5	ASTM G 154
Tear Resistance	NEWTON	58N/5cm	ISO 13937-1
Tensile strength	NEWTON	490N/5cm	ISO 13937-1
Temperature resistance	Celsius	-40°C / +BO°C	------
Air permeability	%	19%	
Inflammable at	Celsius	340°C	

GENERAL REQUIREMENTS:

Packaging	Rolled on 3 inch diameter round cardboard tube. Covered with protective wrapping
Labelling	Product name, product number, length, width
Marking	(to be advised)
Length	(as per order)
Width	(as per order)
Quality	No joins,

As informações contidas na presente ficha são baseadas em conhecimentos considerados válidos, disponibilizados pelo fabricante do produto considerando condições normais de manuseamento e aplicação, não constituindo pela nossa parte uma garantia de resultados obtidos e estando sujeitos à verificação do utilizador. Os valores apresentados poderão variar de acordo com as respectivas especificações.