OBRAS 360 by SOTECNISOL

First Report

Report Date:	11.03.2019
Report No.:	20190311-1

Product Data:		**Delivery:**	
Label:	Eurobent, private label EUROSTRIP	**Weight:**	0.80 kg/m
		Quantity:	5400 m
Quantity per Pallet:	900 m		

Product hEN Standard:	Not covered by European harmonized Standard
Product DIN Standard:	Not covered by German DIN standard

Intended use:	Waterstop for internal joint sealing in concrete members with a high-water penetration resistance against pressing and non-pressing water and against ground moisture in compliance with the Bauregelliste A, Part 2, No. 2.53 or Verwaltungsvorschriften Technische Baubestimmungen (VwV TB), No. 3.3.		
System of assessment:	System 4 (first issued 2001)	**Testing Institute:**	MPA Braunschweig

Properties	Test conditions	Requirements	Intervals
Inspection of source material	Manufacturer's declaration or suitable tests	No signs of change	Per shipment lot
Height Width	- -	18 mm ± 10 % 24 mm ± 10 % or 16 mm ± 10 % 21 mm ± 10 %	Per lot
Density	DIN EN ISO 1183-1 immersion method	1.81 g/cm³ ± 3 %	Per lot

TÜV SÜD ISO 9001
tuev-sued.de
TOP 100 Top-Innovator 2017

The "First Report" is equivalent to a "Declaration of Performance" but only for non-harmonized product standards such as bentonite waterstop tapes.

"Declaration of Performance" can be given only for products according to European harmonized Standards such as membranes (bentonite membranes DIN EN 13491, Pre- applied concrete bonding membranes DIN EN 13967, ...)

First Reports can be given to products having an official General Building Code Test Certificate including Factory Production Control Procedures according to the DIN 18200.

The "First Report" is equal to the "Declaration of Conformity" and the manufacturer confirms the quality of the product.

BPA
WATERPROOFING SYSTEMS
Behringstraße 12
D - 71083 Herrenberg-Gültstein
Tel. +49 (0)7032/89399-0, Fax 89399-29
www.bpa-waterproofing.com

Herrenberg, 11.03.2019

Location / Date | Signature / Company Stamp